

20L EXPLOSION SAFE FUEL CAN

- With UN packaging authorization for packing groups II and III (marking letter Y) and TÜV-mark type certification
- 0,9mm body metal thickness
- High durability external powder coating
- Fuel resistant internal coating
- Filled with aluminium foil mesh, which absorbs the heat and prevents explosion risk
- Cans are regularly tested and comply with Internal pressure test up to 1,0 bar and drop test from 1,2 m height

Additional options:

- Available special markings
- Available separate accessories: pouring spouts, adapters, can holders.
- Colours are available on request according to RAL catalogue:



| SPECIFICATION | Fuel can |
|---------------|----------|
| Depth, mm | 165 |
| Width, mm | 345 |
| Height, mm | 468 |
| Net, kg | 4.8 |

| SPECIFICATION | Box of 5 | Box of 4 |
|---------------|----------|----------|
| Pieces/box | 5 | 4 |
| Depth, mm | 854 | 678 |
| Width, mm | 358 | 358 |
| Height, mm | 488 | 488 |
| Net, kg | 24 | 19,2 |
| Gross, kg | 25,6 | 20,4 |

| SPECIFICATION | Pallet | |
|---------------|--------|------|
| Pieces/pll | 70 | 56 |
| Boxes/pll | 14 | 14 |
| Depth, m | 1,2 | 1,2 |
| Width, m | 0,8 | 0,8 |
| Height, m | 2,60 | 2,49 |
| Net, kg | 336 | 269 |
| Gross, kg | 383 | 311 |

